

**U.S.S.N. 10/071,620**  
**Gholam-Reza Zadno-Azizi, et al**  
**PRELIMINARY AMENDMENT**

CH  
By  
is to be voided, abdominal pressure is used. The threshold pressure is also low enough that the abdominal pressure will overcome the resistance and allow flow. Where placement is in the cardiovascular system, minimum resistance to flow in one direction may be designed into the valve. In this application, however, substantial resistance to flow is designed into the valve to eliminate flow in one direction for all pressures contemplated.

---

**IN THE ABSTRACT**

**Please replace the paragraph on page 16, lines 2-13, with the following:**

---

BS  
A device to provide body fluid flow control in the form of a valve to be located within a duct or passageway. The device is controlled through pressure above a preselected threshold. Bulk resilience about a passageway in a valve body provides the mechanism for controlled flow. One-way valve operation may be provided through a flap or through a pressure differential on the valve body depending upon the direction of flow. A frame structure positioned within a resilient seal includes longitudinally elongated elements which may be of spring material, malleable material or heat recoverable material so as to accomplish an initial insertion state and an expanded anchoring state. A valve support transitions between the resilient seal portion and the valve body to insure that the states do not change the threshold opening pressure. Insertion devices may be employed to position and actuate a change of state of the frame in the body duct or passageway.

---

**U.S.S.N. 10/071,620**  
**Gholam-Reza Zadno-Azizi, et al**  
**Marked up attachment to Preliminary Amendment**

flow is designed into the valve to eliminate flow in one direction for all pressures contemplated.

**IN THE ABSTRACT**

**Please amend the paragraph on page 16, lines 2-13, as follows:**

A device to provide body fluid flow control in the form of a valve to be located within a duct or passageway. The device is controlled through pressure above a preselected threshold. Bulk resilience about a passageway in a valve body provides the mechanism for controlled flow. One-way valve operation may be provided through a flap or through a pressure differential on the valve body depending upon the direction of flow. A frame structure positioned within a resilient seal includes longitudinally [elongate] elongated elements which may be of spring material, malleable material or heat recoverable material so as to accomplish an initial insertion state and an expanded anchoring state. A valve support transitions between the resilient seal portion and the valve body to insure that the states do not change the threshold opening pressure. Insertion devices may be employed to position and actuate a change of state of the frame in the body duct or passageway.